

Grease Duct Access Doors

Single Skin Access Doors



A curved access door installation



A flat access door installation

UL/ULC listed single skin grease duct access doors that meet or exceed all NFPA 96 and mechanical code requirements.

VaughanAir's UL/ULC listed grease duct access doors are available in galvanized steel, 304 stainless steel or 316 stainless steel construction and can be used in zero clearance systems. They come in various shapes and size, including curved designs for installation on round duct.

VaughanAir's UL1978 listed grease doors are light weight and easy to install, as no frame is required and a cut around template sticker is provided. The grease doors require no welding, and no tools are needed for removal or reinstallation. The doors ship with the gasket, rated for 1500°F (816°C), already installed and a single rigid handle which eliminates the misalignment problems so often seen in grease door installations.

Listing Number: UL listing YYXS MH26975

VaughanAir's Grease Duct Access Doors are easy to install and remove and are the perfect solution to allow for proper cleaning of grease duct systems.

Access Door Size Chart

Model	Door (OD)	Door (ID)	Weight (lbs)
1508	15" x 8"	12" x 5"	3
1510	15" x 10"	12" x 7"	4
1512	15" x 12"	12" x 9"	5
2108	21" x 8"	18" x 5"	4
2110	21" x 10"	18" x 7"	5
2112	21" x 12"	18" x 9"	6
2114	21" x 14"	18" x 11"	6
2118	21" x 18"	18" x 15"	8
2323	23" x 23"	20" x 20"	13
2708	27" x 8"	24" x 5"	6
2710	27" x 10"	24" x 7"	6
2712	27" x 12"	24" x 9"	7
2714	27" x 14"	24" x 11"	8
2718	27" x 18"	24" x 15"	9
2723	27" x 23"	24" x 20"	13

Please visit our website at www.vaughanair.com to find your local representative or contact **VaughanAir** for further information at info@vaughanair.com.